

HEAT - L

Technical Specifications | Teknik Özellikler

Body	: Aluminium
Glass	: Tempered
Lens	: PMMA
Light Source	: High Power LED
CRI	: Ra>80
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 7016
Usage	: Wall / Pole
IP	: IP66

Gövde	: Alüminyum
Cam	: Temperli
Lens	: PMMA
Işık Kaynağı	: High Power LED
CRI	: Ra>80
Giriş Gerilimi	: 220-240V AC 50/60Hz
Gövde Rengi	: Ral 7016
Kullanım Şekli	: Duvar / Direk
IP	: IP66

Product Chart | Ürün Tablosu

Product Code	Power	CCT/K	Lumen
SML720.280.E56.00.080.40	80W	4000K	9.600
SML720.280.E56.00.100.40	100W	4000K	12.000
SML720.280.E56.00.120.40	120W	4000K	14.400
SML720.280.E56.00.080.65	80W	6500K	9.600
SML720.280.E56.00.100.65	100W	6500K	12.000
SML720.280.E56.00.120.65	120W	6500K	14.400




Options | Opsiyonlar

DALI Compatible

DALI Uyumlu

Dimensions | Ölçüler



a: 282mm / b:516mm / h: 100mm

Photometric Data | Fotometrik Veri

