



## NORMA

### Technical Specifications | Teknik Özellikler

Body	: Electrostatic Powder Coated DKP Sheet Metal
Reflector	: Aluminium Reflector With High Purity
Light Source	: TL5 Fluorescent Lamp
Ballast	: Electronic Ballast
Input Voltage	: 220-240V AC 50/60Hz
Body Color	: Ral 9016
Usage	: Surface Mounted
IP	: IP20

Gövde	: Elektrostatik Toz Boyalı DKP Sac
Reflektör	: Yüksek Safılıkta Alüminyum Reflektör
Işık Kaynağı	: TL5 Floresan Lamba
Balast	: Elektronik Balast
Giriş Gerilimi	: 220-240V AC 50-60Hz
Gövde Rengi	: Ral 9016
Kullanım Şekli	: Sıva Üstü
IP	: IP20

### Product Chart | Ürün Tablosu

Product Code	Power	LAMP	Cut Out (mm)	a / b / c
SMF111.214 R	2x14W	T15 FLUORESCENT	275x575	295x595x47
SMF111.254 R	2x54W	TL5 FLUORESCENT	275x1175	295x1195x47
SMF111.314 R	3x14W	TL5 FLUORESCENT	575x575	595x595x47
SMF111.414 R	4x14W	TL5 FLUORESCENT	575x575	595x1195x47
SMF111.214 RL	2x8W	TL5 LED TUBE	275x575	295x595x47
SMF111.254 RL	2x26W	TL5 LED TUBE	275x1175	295x1195x47
SMF111.314 RL	3x8W	TL5 LED TUBE	575x575	595x595x47
SMF111.414 RL	4x8W	TL5 LED TUBE	575x575	595x1195x47

### Options | Opsiyonlar

Emergency Unit (1-3 Hour)

Acil Durum Kit'i (1-3 Saat)

### Dimensions | Ölçüler

