



## SPOLA-3&4

### Technical Specifications | Teknik Özellikler

|               |                       |
|---------------|-----------------------|
| Body          | : Aluminium           |
| Diffuser      | : Opal Diffuser       |
| Light Source  | : Mid Power LED       |
| CRI           | : Ra>80               |
| Input Voltage | : 220-240V AC 50/60Hz |
| Body Color    | : Ral 9003            |
| Frame Color   | : Ral 9003            |
| Usage         | : Recessed Ceiling    |
| IP            | : IP20 / IP40         |

|                |                       |
|----------------|-----------------------|
| Gövde          | : Alüminyum           |
| Difüzör        | : Opal Difüzör        |
| Isık Kaynağı   | : Mid Power LED       |
| CRI            | : Ra>80               |
| Giris Gerilimi | : 220-240V AC 50/60Hz |
| Gövde Rengi    | : Ral 9003            |
| Çerçeve Rengi  | : Ral 9003            |
| Kullanma Şekli | : Sıva Altı           |
| IP             | : IP20 / IP40         |


### Product Chart | Ürün Tablosu

| Product Code            | Power | CCT  | Lumen |
|-------------------------|-------|------|-------|
| SML361.103.D13.00.06.30 | 6W    | 3000 | 618   |
| SML361.103.D13.00.06.40 | 6W    | 4000 | 654   |
| SML361.103.D13.00.06.65 | 6W    | 6500 | 654   |
| SML361.104.D13.00.12.30 | 12W   | 3000 | 1236  |
| SML361.104.D13.00.12.40 | 12W   | 4000 | 1308  |
| SML361.104.D13.00.12.65 | 12W   | 6500 | 1308  |


### Options | Opsiyonlar

|                              |
|------------------------------|
| Sensor Compatible            |
| DALI Compatible              |
| Emergency Unit : (1-3 Hour)  |
| Sensör Uyumlu                |
| DALI Uyumlu                  |
| Acil Durum Kiti : (1-3 Saat) |

### Dimensions | Ölçüler



a:90mm / b:100mm



a:120mm / b:100mm

### Photometric Data | Fotometrik Veri

